





REV	DESCRIPTION	DATE
1.00	INITIAL DESIGN	2016/08/15
1.10	NEW DRAWING FRAME	2025/01/14



RECOMMENDED
STRIP LENGTHS



MECHANICAL DATA
DURABILITY : 100 CYCLES
TEMPERATURE RANGE : -65°C ~ + 165°C

ELECTRICAL DATA
FREQUENCY RANGE: DC~6GHz
IMPEDANCE : 50Ω
VSWR : 1.5 MAX.
WORKING VOLTAGE : AC 500V
WITHSTANDING VOLTAGE : AC 1500V
INSULATION RESISTANCE : 5000 MΩ MIN

05	FERRULE	BRASS	NICKEL	1
04	WASHER	BRASS	NICKEL	1
03	CENTER PIN	P.BRONZE	GOLD	1
02	INSULATOR	TEFLON	NONE	1
01	BODY	BRASS	NICKEL	1
NO	DESCRIPTION	MATERIAL	FINISH	Q'TY

TITLE TNC(F) st. crimp type for LMR300, Nickel			DWG NO. C18CA3FL30008B			CUST. P/N: N/A DWG NO: N/A			GENERAL TOLERANCES .X ±0.2 .XX ±0.2 .XXX ±0.2 ANGLES N/A			DRAWN BY: Kelly 2025/01/14 CHK'D BY: Chilli 2025/01/14 DA2501140009			REV. 1.10		
SHEET 1 of 1			Unit: mm														